



FABRIANO COCKTAIL



TECHNICAL SPECIFICATIONS					
	Thickness	Taber Stiffness °15		Strength	
GSM	ISO 534 µm	long 10%	trav 10%	long 10%	trav 10%
120	144	21	11	9.2	5.8
290	363	280	140	16	9.5

STOCK RANGE		
GSM	450 x 640	710 x 1000
120	•	•
290	•	•

* 48 hour delivery on this range

FINISHING SUITABILITY							
Laminate	Spot UV	Varnish	Foil Block	Folding	Die Cut	Embossing	Scoring
✓	✓	✓	✓	✓	✓	✓	✓

PRINTING PROCESSES	
Litho	
✓	

SUSTAINABILITY STATEMENT						
	PULP		ENVIRONMENTAL	QUALITY	ENERGY	H&S
FSC	ECF	EUTR	ISO 14001	ISO 9001	ISO 50001	OHSAS 18001
✓	✓	✓	✓	✓	✓	✓

PRODUCT COMPLIANCE		
EUTR EU (995/2010)	✓	Manufactured in the EU. Full due diligence relating to legal sourcing of timber has been performed
Modern Slavery Act	✓	Supply chain for this product has been fully risk assessed
Pulp Traceability	✓	Full details available on request
REACH	✓	Fulfils requirements - EU (1907/2006) for Registration, Evaluation and Authorisation of Chemicals
Product Safety	✓	Certificate available on request