



Sustainability

Pulp			Environmental		Quality	H&S
FSC®	ECF	ORIGIN	EMAS	ISO 14001	ISO 9001	OHSAS 18001
✓	v	*	✓	✓	*	v

ECF Elemental Chlorine Free

FSC® Forest Stewardship Council ® Forest management certification scheme

ORIGIN Identification of tree species used for pulp manufacture obtainable on request

EMAS Eco-Management and Audit System

ISO 14001 International standard for environmental management

ISO 9001 International standard for quality management

OHSAS 18001 International standard for health & Safety management

Finishing Suitability

Laminate	Varnish	Foil Block	Folding	Die Cut	Emboss	Scoring
*	*	*	*	✓	*	*

Technical Specifications

Weight	g/m²	60	70	80	90	100	120
Thickness	μm	76	89	99	110	122	145
Bulk	ISO 534 cm3/g	1.27	1.28	1.24	1.22	1.22	1.21
Whiteness	CIE	143	143	143	143	143	143
Roughness	Bendtsen	160	160	160	160	160	160
Opacity	ISO 2471 %	86	90	92	94	95	96

A widers ubstance range is available on makings and mill direct deliveries.

Stock Range

g/m²	450 x 640	630 x 880	640 x 900
80	*	*	\
90	4	4	*
100	*	*	*
120	4		V

Print Suitability

Litho	HSWO*	CutStar*	Digital**
*	*	*	✓

^{*} Available on an ex-mill basis

Published – 1st February 2020



^{**} Compatible for most dry toner digital presses