

Fixter



TECHNICAL SPECIFICATIONS				
Face Material		Backing Sheet		
Vellum Extra (Uncoated)				
Grammage	70	Grammage	82	
Thickness	75	Thickness	85	
Whiteness	113	Strength	MD>6	
Dry Opacity	85		/ CD>4.5	

Coated (Gloss)				
Grammage	80	Grammage	82	
Thickness	58	Thickness	85	
Whiteness	95	Strength	MD>6	
Dry Opacity	88		/ CD>4.5	

STOCK RANGE				
Coated				
	450 x 320	450 x 640	520 x 720	
Solid Back		•	•	
Split Back		•	•	

Vellum Extra (Uncoated)				
	450 x 320	450 x 640	520 x 720	
Solid Back	•	•	•	
Split Back		•	•	

			FINISHING S	SUITABILITY	•		
Laminate	Spot UV	Varnish	Foil Block	Folding	Die Cut	Embossing	Scoring
✓	✓	✓	✓	✓	✓	✓	✓

PRINTING PROCESSES			
Litho	Laser Digital		
✓	✓		





Fixter



SUSTAINABILITY STATEMENT					
	PULP		ENVIRONMENTAL	QUALITY	H&S
FSC	ECF	EUTR	ISO 14001	ISO 9001	OHSAS 18001
✓	✓	✓	✓	✓	✓

PRODUCT COMPLIANCE		
EUTR EU (995/2010)	✓	Manufactured in the EU. Full due diligence relating to legal sourcing of timber has been performed
Modern Slavery Act	✓	Supply chain for this product has been fully risk assessed
Pulp Traceability	✓	Full details available on request
REACH	✓	Fulfils requirements - EU (1907/2006) for Registration, Evaluation and Authorisation of Chemicals
Product Safety	✓	Certificate available on request

