

# **UPM** Fine SC



### Stock Range

g/m²	450 x 640	520 x 720	640 x 900	720 x 1020
100	✓			*
120	<b>*</b>		<b>*</b>	✓
150	<b>*</b>	✓	✓	<b>√</b>
190	<b>*</b>	✓		
250	✓	✓	<b>*</b>	✓

### **Technical Specifications**

Weight	g/m²	100	120	150	190	250
Whiteness	CIE %	150	150	150	150	150
Thickness	μm	90	106	133	173	225
Bulk	180534 cm <sup>3</sup> /g	0.9	0.88	0.89	0.91	0.9
Brightness	ISO 2470-2 %	103	103	103	103	103
Roughness	ISO 8791-4	35	35	35	35	35
Opacity	ISO2471%	94	96	97.5	99	99.5





## **UPM** Fine SC



#### **Print Processes**

Litho	Digital	HSWO	CutStar
✓	<b>*</b> *	<b>√</b> **	<b>√</b> **

<sup>\*</sup> compatible for most digital processes

### Finishing Suitability

Laminate	Varnish	Foil Block	Folding	Die Cut	Emboss	Scoring
✓	<b>*</b>	*	*	*	<b>*</b>	*

### Sustainability

	Pulp		Environmental			Quality, Health & Safety			
FSC®	ECF	ORIGIN	EMAS	EU Ecolabel	ISO 14001	ISO 9001	ISO 50001	OHSAS 18001	
✓	✓	✓	<b>*</b>	<b>*</b>	✓	<b>*</b>	<b>*</b>	✓	

ECF Elemental Chlorine Free

FSC® Forest Stewardship Council ® Forest management certification scheme

ORIGIN Identification of tree species used for pulp manufacture obtainable on request

EU Ecolabel European environmental award for overall environmental performance

ISO 14001 International standard for environmental management

ISO 9001 International standard for quality management
ISO 50001 International standard for energy management

OHSAS 18001 International standard for health & safety management

Updated: 22<sup>nd</sup> February 2019



<sup>\*\*</sup> available on an ex-mill basis